



<p><b>1</b></p> <p>Apply teflon tape to threaded tail.</p> <p>620mm to 680mm recommended top and bottom mounting distance.</p> <p>For masonry and tiled walls, drill a 8mm hole for supplied plastic wall plug. For plasterboard, use a toggle type fastener (not supplied).</p>	<p><b>2</b></p> <p><b>TOP MOUNTING</b>        Place Dress Plate and O Ring over threaded tail. Screw Inlet Adaptor onto threaded tail. Tighten Firmly.</p> <p><b>BOTTOM MOUNTING</b>        Push Wall plug into drilled hole. Fit Lower Mounting Pillar, Dress Plate and O ring over the Wall Plug and screw in place with screw. Tighten firmly.</p>	<p><b>3</b></p> <p>Upper Pillar, Grub Screw, Riser, Lower Pillar, Grub Screw</p> <div style="border: 1px solid black; padding: 5px;"> <p>Note: Shower Rail is shipped as an installed assembly. If disassembly is required, please refer to diagram.</p> </div>
<p><b>4</b></p> <p>Grub Screw x 2, Rail Assembly, Grub Screw x 1</p> <p>Push Shower Rail Assembly onto Mounting Flanges. Tighten Grub Screws firmly.</p>	<p><b>5</b></p> <p>Ensure Rubber Washers are inserted into Hose.</p> <p>Screw Shower Hose to Hand Shower and Shower Rail.</p> <p>Hand Shower, Rubber Washer, Connect hand shower to hose.</p> <p>Thick Rubber Washer</p>	

recommended working pressure  
**150-500KPa**  
 maximum hot water temperature  
**75 degrees**

**NOTE:**

- If the pressure exceeds or is likely to exceed 550kPa, an approved pressure limiting device must be installed.
- Flush out all pipe work prior to installation.
- If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
- Installation should comply with Australian standard AS3500.1 or relevant local authority requirements. Showers may not be suitable for use within:
  - Gravity-fed water systems
  - Some instantaneous hot water systems; or

• Pressure supply less than 150kPa;  
 NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.

Any flow controller incorporated in the outlet to be tightened to prevent removal by hand. As Per AS3718

Failure to comply with the above may void all warranties.

**WARRANTY:**  
 Please refer to the full warranty statement enclosed with the product before installing.

**MAINTENANCE AND CARE:**

- Chrome plated surfaces should be cleaned with mild liquid detergent or soap and water.
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

**DISCLAIMER:**  
 While we aim to ensure the specifications shown are correct at the time of printing, we reserve the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

\*All measurements are shown in millimeters.